



RF-4100

Lower C-Band Interchangeable Frequency Module



SPECIFICATIONS

Frequency Range

4400 - 5000 MHz

RF Modulation

OFDM (64QAM, 16QAM, QPSK, BPSK)

Antenna Chains

3 Independent RF Chains

TX/RX Operating Modes

All MIMO modes from SISO to 3x3

Channel Bandwidth

5, 10, and 20 MHz

Software Configurable

Peak TCP Throughput

120 Mbps at 20 MHz Channel

MIMO Techniques

Maximal Ratio Combining

Space-Time Block Coding

Spatial Multiplexing

Max. Aggregate Transmit Power

6W (2W per RF Chain)

Antenna Ports

(3) SMP (50 Ohms)

TX Power Control

33 to 16.5 dBm, 0.5 dB per step

Power Control Accuracy

+/- 2 dB

Frequency Accuracy

+/- 4 ppm, max.

Minimum Receiver Sensitivity

-95 dBm at 5 MHz bandwidth, BPSK

Max. RF Input

-10 dBm

Max. RF Input without Damage

+10 dBm

Max. Peak Power Consumption, TX

50W

Power Consumption, RX

6W

Operating Temperature

-40°C to +85°C

ESD Protection

+/- 8KV Contact discharge, per IEC 6100-4-2

Dimensions

4.0 x 2.6 x 1.4 in.

10.3 x 6.6 x 1.4 cm

Weight

6.98 oz.

197 g

RELEASABLE

Persistent Systems, LLC | 303 Fifth Avenue, Suite 306 | New York, NY 10016 | O 212-561-5895 | F 212-202-3625

persistentsystems.com