



Multi-Band Tracking Antenna



TRK-AUTO-SYS-02

Portable, High-Performance Datalink for Manned or Unmanned Aircraft

The Multi-Band Tracking Antenna delivers the throughput to go the distance. Operate with up to two MPU5s for frequency redundancy with any aircraft up to 120+ miles.

Long Range & High Throughput

- MIMO technology for high-bandwidth connectivity and reliability
- 360° continuous rotation & <1° pointing accuracy for optimal, bidirectional communication
- Operate in L-, S-, and C-Bands without switching feeds
- Dual band operation with two MPU5s or one MPU5 with a third party radio

Resilience & Robustness

- If one band becomes too congested, the other will continue to track without reconfiguration
- Continue tracking aircraft in GPS-denied environments

Portable, Lightweight, & Durable

- Two-person setup in <15 minutes
- Rugged design for performance in harsh conditions

The Soldier Empowered with Information

- Stream HD Video & IP Data from aircraft over long distances
- Meet growing data exfiltration requirements
- Layer 2 connectivity between payloads and the enterprise

NO NDA REQUIRED

persistentsystems.com

© 2006 - 2023 Persistent Systems, LLC. All rights reserved. The Wave Relay® logo, the Persistent Systems, LLC logo and other designated trademarks and trade names are the property of Persistent Systems, LLC or their respective owners. Product specifications are subject to change without notice. This material is provided for informational purposes only; Persistent Systems, LLC assumes no liability related to its use and expressly disclaims any implied warranties of merchantability or fitness for any particular purpose.

The export and/or the release of certain products, technology and software to non-US persons might be subject to export restrictions. Please refer to the US export laws & regulations for details.



PERSISTENT SYSTEMS

SYSTEM SPECIFICATIONS

RF

Antenna Gain
L-Band: 20.8 dBi
S-Band: 25 dBi
Lower C-Band: 28.3 dBi
Upper C-Band: 30.5 dBi

Beamwidth
L-Band: 11.5°
S-Band: 6°
Lower C-Band: 3.5°
Upper C-Band: 2.25°

Polarization
Dual Polarized
Twist-lock change between Vertical/Horizontal and
Slant 45° polarization


Feed Frequency Range
1.2 - 6 GHz
Single Tri-Band Feed for all RF Module frequencies

RF Module Compatibility	
Freq. (MHz)	RF Module P/N
1350 - 1390 MHz	RF-1150
2025 - 2145 MHz	RF-2125
2200 - 2507 MHz	RF-2150
4400 - 5000 MHz	RF-4100
5100 - 6000 MHz	RF-5100

The Multi-Band Tracker supports 3rd party radios that operate in this frequency range

Note: MPU5s not included. The Multi-Band Tracking Antenna only supports data-in-transit and does not provide native data processing or storage.

PHYSICAL



Weight
124.54 lbs. / 56.5 kg (system only)
269.2 lbs. / 122.1 kg (in cases)

Color
Black

Number of Cases
(5) rollable carrying cases with custom foam

Total Case Volume
30.7 ft³

Assembly/Setup Time (not including configuration)
15 minutes, 2 person

OPERATIONAL

Elevation
-5° to +80°

Pan
360° continuous rotation

Pointing Accuracy
<1°

Calibration
Self-calibration via automatic heading system

ELECTRICAL

Input Voltage
100 - 240 VAC
18-34 VDC (Compatible with BB-2557, BB-2590, and BA-5590 batteries or equivalent)

Max. Power Consumption
240W

ENVIRONMENTAL

Operating Temperature
-15°C to +55°C

Environmental
IP67

Note: Not RoHS compliant